







SÉRIE C4 10

- PFA 16
- Brides tournantes
- ISO PN 10
- DN 80, 8 trous

COUDES À BRIDES




DN	L mm	Poids kg	Code	P.U. € H.T
1/4 (90°)				
60 percé 60/65	160	8,3	105015	172,45
80	165	11,1	105100	206,43
100	180	14,2	105200	243,29
125	200	19,6	105300	325,69
150	220	26,4	105400	452,01
200	260	33,9	105500	674,06
250	350	67,3	105550	1 290,62
300	400	87,6	105600	1 700,39
1/8 (45°)				
60 percé 60/65	160	7,9	105815	172,45
80	130	12,1	105900	206,43
100	140	13	106000	238,83
125	150	16,8	106100	291,07
150	160	21,4	106200	427,29
200	180	32,6	106300	639,83
250	245	56,3	106310	891,48
300	275	77,6	106315	1 292,81
1/16 (22,5°)				
60 percé 60/65	115	7,4	106464	172,45
80	105	8,8	106468	206,43
100	110	12	106470	238,83
125	105	14,9	106472	289,26
150	110	18,7	106474	427,29
200	130	30,2	106476	639,83
250	140	49,5	106478	876,48
300	175	61,6	106480	1 292,81
1/32 (11,25°)				
60 percé 60/65	120	7,1	106482	172,45
80	115	9,7	106486	206,43
100	115	12,6	106488	238,83
125	110	15,4	106490	289,26
150	115	19,3	106492	427,29
200	130	28	106494	639,83
250	105	35,8	106496	876,48
300	175	54,2	106498	1 292,81



SÉRIE C4 15

- PFA 16
- Brides tournantes
- ISO PN 10
- DN 80, 8 trous
- Autres longueurs, nous consulter

MANCHETTES À BRIDES



DN	L mm	Poids kg	Code	P.U. € H.T
0,25 m				
60 percé 60/65	250	7,6	106515	158,84
80	250	9,9	106600	187,99
100	250	12,3	106700	181,39
125	250	16,3	106800	267,29
150	250	19,9	106900	376,84
200	250	27,9	107000	571,88
250	250	37,1	107010	753,78
300	250	51,1	107020	1 313,00
0,50 m				
60 percé 60/65	500	10,8	107215	232,27
80	500	14,0	107300	245,43
100	500	16,7	107400	285,52
125	500	23,6	107500	382,33
150	500	28,3	107600	464,85
200	500	37,6	107700	637,48
250	500	54,3	107725	1 047,40
300	500	72,1	107730	1 838,27

