


FICHE TECHNIQUE PORTE-MOUSQUETONS "POMPIER"

Acier zingué



Dimensions : tolérance $\pm 0,2$ mm

CODE	CODE EAN	X PIECE VRAC GENCODE	X PIECE SACHET VRAC	X PIECE SACHET	X PIECE BLISTER	X PIECE BARQUETTE	Ø Fil D (mm)	A (mm)	C (mm)	L (mm)	CHARGE DE TRAVAIL INDICATIVE (en kg)
120G4Z	3233690237525	1					4	6	5,5	40	75
120/40Z	3233690033288		10				4	6	5,5	40	75
PO10	3233690207238				2		4	6	5,5	40	75
PO104	3233690244479				4		4	6	5,5	40	75
120/50Z	3233690045410		10				5	8	7	50	100
120G5Z	3233690237532	1					5	8	7	50	100
PO00	3233690029052				1		5	8	7	50	100
PO002	3233690244455				2		5	8	7	50	100
VPO00	3233690072591			1			5	8	7	50	100
120/60Z	3233690000723		10				6	9,5	8	60	150
120G6Z	3233690237549	1					6	9,5	8	60	150
PO1	3233690029069				1		6	9,5	8	60	150
PO12	3233690244462				2		6	9,5	8	60	150
VPO1	3233690072607			1			6	9,5	8	60	150
BAR14	3233690049616					20	6	9,5	8	60	150
120/80Z	3233690000730		10				8	12	9	80	250
120G8Z	3233690237556	1					8	12	9	80	250
PO2	3233690029076				1		8	12	9	80	250
PO22	3233690244486				2		8	12	9	80	250
VPO2	3233690072621			1			8	12	9	80	250
120/100Z	3233690000679		5				10	14	12	100	300
120G-10Z	3233690236856	1					10	14	12	100	300
PO3	3233690029083				1		10	14	12	100	300
PO32	3233690244493				2		10	14	12	100	300
VPO3	3233690072638			1			10	14	12	100	300
120G11Z	3233690279266	1					11	18	17	120	400



Ne pas utiliser pour le levage et la suspension humaine