



SIHJ10CI

FLOOR DRAIN, 304 STAINLESS STEEL GRATING AND FRAME

BASIC FUNCTION :

- This floor drain is aimed at collecting discharge waters of loggias, courtyards, bathrooms, laundry rooms...



DESCRIPTION :

- This body of the gully is made of injected white PVC.
- The 100 x 100 mm grating is made of 304 stainless steel (lockable on request).
- The 93 mm * external diameter allows a perfect connection with a \varnothing 100 mm male pipe.
- Includes 2 vertical sockets (diameters 50 mm & 40 mm) for a maximum 57 mm recess.

* Internal \varnothing of a \varnothing 100 pipe.

TECHNICAL CHARACTERISTICS :

- Water seal height : 28 mm.
- Flow rate : 0,7 liter/second.
- Resistance class : H 1,5.

ACCESSORIES :

- An horizontal PVC adaptor DN 40/50 mm (ADSIHJ) is available in case of space-saving requirement.

IMPLEMENTATION :

- The \varnothing 93 mm body enables a connection to a \varnothing 100 male pipe, \varnothing 50 female or \varnothing 40 male. Those PVC / PVC connections ensure a perfect sealing.
- In case of sealing in concrete, make sure that the gully body is well positionned and in full contact with the concrete.

